A002: SELSTAT

high solids antistatic metallised polish

Description of product

High performance dissipative floor polish. Retains performance even at humidities as low as 11% Independently tested to IEC 61340 - 4 - 1 and BS 7506. Makes charge dissipate off a standard vinyl floor. Improves the conductivity of conductive flooring. Applies, hardens and protects like a normal floor polish. Non-slip

Product Uses

For all linoleum, P.V.C., rubber, sealed cork, sealed wood, terrazzo and thermoplastic floors. N.B. Not suitable for unsealed wood, unsealed cork or laminate flooring.

Selstat must be applied to a clean grease free floor. Strip old polish with Selate then rinse thoroughly with clean water, allow floor to dry. Apply a thin even film of Selstat using a clean lint free mop or applicator. Apply a second coat when the first is dry (approximately 30 minutes). COVERAGE: 60 square metres per litre. Full independent test reports are available on our website. N.B. Buffing is not recommended as this will reduce the static dissipative property of the polsh.

iNsight Supported

iNsight is Selden's interactive product selection and training system. Enables the user to create full COSHH training kits, wallcharts, task cards and more. visit http://www.selden.co.uk/insight

iNsight recommended product uses

Flooring - applying floor polish (mop application)



Product Hazards and PPE Requirements

Contains: Benzisothiazolinone

Risk Phrases

Contains Benzisothiazolinone May produce an allergic reaction

Safety Phrases

Technical Data

A blend of acrylic copolymers, resins and coploymer wax incorporating a antistat agent, wetting agents and film forming aids in a stable water based emulsion form incorporating metal cross linking additives.

Appearance Opaque liquid

Colour white Viscosity <10 cps 1.028 Density 8.0 - 8.2 рН

Activity Fragrance

Characteristic, slightly sweet Stability 2 years in unopened containers Storage Protect from freezing

Environmental Profile

Biodegradability

All surfactants contained in Selden Products meet the requirements of the EU Detergent Directive 2005 -2004/648/EC. This requires all surfactants to break down both • If it can be recycled, it will be recycled. quickly and completely into harmless material such as CO2 . Our chemicals policy exceeds regulatory requirements. and water

Selden Environmental Charter

- . We set ourselves industryleading standards.
- · Selden minimises wastage, packaging and transportation.

- . We don't expect other people to clean up after us. · Conserving energy, preserving resources.
- . By being innovative, we strive to do better.
- . We like to work in partnership with our clients
- Visit our website for more information

External Accreditations

9001 - Quality System 14001 - Environmental System

18001 - Health & Safety System IPPC Certified Manufacturer

Sustainability Product conforms with the DEFRA endorsed Sustainable Cleaning

quidance

COSHH+ Supported

Selden's bespoke COSHH awareness and product training tool. Users specify the products in use and instantly generate a full training pack to enable quick and effective staff training.



www.flagship-mcp.com

Flagship products are those products that are included in Selden Multi-language Cleaning Programme. Flagship products have induction kits, best practise guidance, MSDS, wallcharts and usage guides available in the



english, french, spanish, portuguese, polish, german, dutch, russian, romanian, estonian, czech, croatian.

Selden Research Limited

Staden Business Park, Staden Lane, Buxton

Derbyshire, SK17 9RZ

Tel: 01298 26226 | Fax: 01298 26540 | Email: info@selden.co.uk | web: www.selden.co.uk















accredited testing laboratory No. 4204



SELDEN

formulating testing manufacturing

the highest standards